



VT-FORS GOLD ARTIC TRAILER

Bespoke kit built specifically for Artic Vehicle types with a trailer.

THIS KIT INCLUDES THE FOLLOWING:

- 1. VT5500-G-1TB**
5CH MDVR
Includes 1TB Hard-drive



- 2. VT-C20-MINI****
Forward-facing Camera



- 3. VT-LT ALERT**
Left-turn Alert



- 4. VT-CAN-M8***
Side Scan Interface
(Vehicle 2012 or newer)



- 5. VT-WNREVERSINGALARM**
White Noise
Reversing Alarm



- 6. VT-TIMER CUT OUT**
Timer cut-out button



- 7. VT-M4-7-AHD (Kit)**
4CH AHD Monitor
Includes 5M Cable, F2F Convertor, Brackets



- 8. VT408-AHD x2**
HD Side-View Camera



- 9. VT408 Spacer 50mm x2
VT408 Spacer 25mm x2**



- 10. VT-SIDE SCAN**
VT-Sensor Brain (No Sensors)
VT-Sensor Display + Mixture of x4 sensors



- 11. VT-CORNER SCAN**
VT-Sensor Brain (No Sensors)
VT-Sensor Display + x4 flush sensors



- 12. VT646-AHD x2****
Rear-view
Camera



- 13. VT-WARNING STICKER
BLIND SPOT
Vehicle Signage**



- 14. VT-C5M x3
VT-C15M x1
VT-C20M x1**



- 15. VT-SUZI**
Cable for
Trailer Camera



- 16. VT-C-MALE TO FEMALE**
Camera input splitter
for trailer camera



- 17. VT-IMAGE SPLITTER (AUTO)**
Image Splitter



KEY FEATURES:

VT5500-G

- Supports 4 channels AHD (1080P) +1 channel IPC (1080P)
- Supports hard disk for main recording
- Alarm integration for central monitoring
- Supports GPS and 3G/4G
- Built-in three-axis inertial sensor
- Vibration-resistant design



VT-LT ALERT

- Dual voltage 12-24 volts
- Bracket Mounted (2 Bolt Fixing)
- M.I.R.A. tested for all on and off road applications
- CE and emc marked
- Epoxy sealed for greater durability against water and vibration
- Pressure washable – IP6



VT-TIMER CUT OUT

- Six minute timer cut-out
- Auto Reset
- 12-14V
- IP67 rated - sealed against mud, water and vibration
- 30(H) x 88(W) x 47(D) mm



VT408-AHD

- DC 12V~24V
- 120°
- 62(L) x 44(H) x 62(W) (mm)
- 20°C + 70°C
- 1280 x 720 pixels



VT-SIDE SCAN

- 4 sensors mixed sensors
- PCB built into sensors
- Splash-proof ECU
- Digital distance display w/buzzer
- DSM scanning technology
- Dual voltage

VT-CORNER SCAN

- 4 Flush sensors
- PCB built into sensors
- Splash-proof ECU
- Digital distance display w/buzzer
- DSM scanning technology
- Dual voltage

VT-C20-MINI

- 1/2.8" SONY 2.13-megapixel
- 1920 x 1080 resolution
- 0.05 Lux/F1.2 (Auto Gain on)
- 3.6mm
- DC 12V±10%
- 90(L) x 46(H) x 70(W)mm



VT-WNREVERSINGALARM

- Epoxy-sealed for greater durability
- Minimum 85 dB output
- M.I.R.A. tested for all on and off-road applications
- Pressure washable – IP67
- 2 Wire



VT-M4-7-AHD (Kit)

- 10.1-inch digital screen
- Resolution 1024 x 600p
- 4 video inputs and 4 trigger wires
- Power voltage of DC10V~36V
- 352(L) x 166(W) x 32(D) mm



VT408 Spacer 50mm

- 65(L) x 50(H) x 55(W) (mm)



VT408 Spacer 25mm

- 65(L) x 25(H) x 55(W) (mm)



VT646-AHD

- 1/3" colour lens
- 1280 x 720 resolution
- 120° wide-viewing angle)
- IR night vision
- 50(L) x 50(H) x 80(W)mm



VT-WARNING STICKER BLIND SPOT



*Additional charges may be involved.
**Not required for FORS but VisionTrack recommend.
For more information please go to www.visiontrack.com

