



Warning Signage

# VT-FORS GOLD RIGID

Bespoke kit built specifically for rigid vehicle types. This kit covers FORS and DVS requirements.

## THIS KIT INCLUDES THE FOLLOWING:

- |   |  |  |  |   |  |
|---|--|--|--|---|--|
| 1. VT5500-G-1TB<br>5CH MDVR<br>Includes 1TB Hard-drive  |  | 2. VT-C20-MINI**<br>Forward-facing Camera                  |  | 3. VT-LT ALERT<br>Left-turn Alert               |  |
| 4. VT-CAN-M8*<br>Side Scan Interface<br>(Vehicle 2012 or newer)                               |  | 5. VT-WNREVERSINGALARM**<br>White Noise<br>Reversing Alarm |  | 6. VT-TIMER CUT OUT<br>Timer cut-out button     |  |
| 7. VT-M4-7-AHD (Kit)<br>4CH AHD Monitor<br>Includes 5M Cable, F2F Convertor, Brackets         |  | 8. VT408-AHD x2<br>HD Side-View Camera                     |  | 9. VT408 Spacer 50mm x2<br>VT408 Spacer 25mm x2 |  |
| 10. VT-SIDE SCAN<br>VT-Sensor Brain (No Sensors)<br>VT-Sensor Display + Mixture of x4 sensors |  | 11. VT646-AHD<br>Rear-view<br>Camera                       |  |   |  |
| 12. VT-WARNING STICKER<br>BLIND SPOT<br>Vehicle Signage                                       |  | 13. VT-C5M x3<br>5 Metre Cable                             |  | 14. VT-C15M<br>15 Metre Cable                   |  |

Product specifications can be found on the next page of this documents.

\*additional charge may be involved.

\*\*Not required for FORS but VisionTrack recommend

### KEY FEATURES:

#### VT5500-G

- Supports 4 channels AHD (1080P) +1 channel IPC (1080P)
- Supports hard disk for main recording
- Alarm integration for central monitoring
- Supports GPS, Wi-Fi and 3G/4G
- Built-in three-axis inertial sensor
- Vibration-resistant design



#### VT-LT ALERT

- Dual Voltage
- CE and EMC approved
- M.I.R.A. - tested for all on-and-off highway applications
- Epoxy sealed for greater durability against water
- Complete with anti-vibration gasket and mounting screws
- 10R approved - 10R-037568



#### VT-TIMER CUT OUT

- Six minute timer cut-out
- Auto Reset
- 12-14V
- IP67 rated - sealed against mud, water and vibration
- 30(H) x 88(W) x 47(D) mm



#### VT408-AHD

- DC 12V~24V
- 120°
- 62(L) x 44(H) x 62(W) (mm)
- 20°C + 70°C
- 1280 x 720 pixels



#### VT-SIDE SCAN

- 4 sensors mixed sensors (Flush/Non-Flush)
- PCB built into sensors
- Splash-proof ECU
- Digital distance display with buzzer
- DSM scanning technology
- Dual voltage



#### VT-WARNING STICKER BLIND SPOT



#### VT-C20-MINI

- 1/2.8" SONY 2.13-megapixel
- 1920 x 1080 resolution
- 0.05 Lux/F1.2 (Auto Gain on)
- 3.6mm
- DC 12V±10%
- 90(L) x 46(H) x 70(W)mm



#### VT-WNREVERSINGALARM

- Epoxy-sealed for greater durability
- Minimum 85 dB output
- M.I.R.A. tested for all on and off-road applications
- Pressure washable - IP67
- 2 Wire



#### VT-M4-7-AHD (Kit)

- 10.1-inch digital screen
- Resolution 1024 x 600p
- 4 video inputs and 4 trigger wires
- Power voltage of DC10V~36V
- 352(L) x 166(W) x 32(D) mm



#### VT408 Spacer 50mm

- 65(L) x 50(H) x 55(W) (mm)



#### VT408 Spacer 25mm

- 65(L) x 25(H) x 55(W) (mm)



#### VT646-AHD

- 1/3" colour lens
- 1280 x 720 resolution
- 120° wide-viewing angle
- IR night vision
- 50(L) x 50(H) x 80(W)mm



For more information please go to [www.visiontrack.com](http://www.visiontrack.com)